

**Section 1 - Identification of The Material and Supplier**

Custom Surface Solutions  
6/3 Tollis Place, Seven Hills  
NSW 2147 Australia

Phone: 1300 AQUA MIX (2782 649)  
Fax: 02 9674 6029  
info@aquamix.com.au

**Chemical nature:** Blend of solvents.  
**Trade Name:** Aqua Mix Sealer and Coating Remover  
**Product Code:** F3547  
**Product Use:** Cleaning preparation.  
**Creation Date:** May, 2012  
**This version issued:** May, 2012 and is valid for 5 years from this date.

**Section 2 - Hazards Identification****Statement of Hazardous Nature**

This product is classified as: Xn, Harmful. Xi, Irritating. N, Dangerous to the environment. Hazardous according to the criteria of SWA.

Not a Dangerous Good according to the Australian Dangerous Goods (ADG) Code. However, this is a C1 Combustible Liquid and for storage meets the definition of Dangerous Goods.

**Risk Phrases:** R53, R66, R67, R20/21/22, R36/38. May cause long term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Harmful by inhalation, in contact with skin, and if swallowed. Irritating to eyes and skin.

**Safety Phrases:** S2, S20, S23, S26, S28, S38, S45, S24/25, S36/37. Keep out of reach of children. When using, do not eat or drink. Do not breathe vapours or mists. In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre. After contact with skin, wash immediately with plenty of soap and water. In case of insufficient ventilation, wear suitable respiratory equipment. In case of accident or if you feel unwell, contact a doctor or Poisons Information Centre immediately (show this MSDS where possible). Avoid contact with skin and eyes. Wear suitable protective clothing and gloves.

**SUSMP Classification:** S6

**ADG Classification:** None allocated. Not a Dangerous Good under the ADG Code.

**UN Number:** None allocated.

**Emergency Overview**

**Physical Description & Colour:** Clear, colourless liquid.

**Odour:** Characteristic odour.

**Major Health Hazards:** 2-butoxyethanol is a severe eye irritant. Results of skin irritation studies are conflicting; however, it is considered to be a mild to moderate skin irritant in test animals. Contact dermatitis has been reported in a few cases. It is well absorbed via the inhalational, oral and dermal routes. This product is harmful by inhalation, in contact with skin, and if swallowed, irritating to eyes and skin, repeated exposure may cause skin dryness or cracking, vapours may cause drowsiness and dizziness.

**Potential Health Effects****Inhalation:**

**Short Term Exposure:** High vapour pressures may cause drowsiness and dizziness. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** Vapours may cause drowsiness and dizziness.

**Skin Contact:**

**Short Term Exposure:** Available data shows that this product is harmful, but symptoms are not available. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

**Long Term Exposure:** Repeated exposure may cause skin dryness or cracking.

**Eye Contact:**

**Short Term Exposure:** This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

**SAFETY DATA SHEET**

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

### Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. Available data shows that this product is harmful, but symptoms are not available. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

**Long Term Exposure:** No data for health effects associated with long term ingestion.

### Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** 2-butoxyethanol is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

## Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
2-Butoxyethanol	111-76-2	10-30	96.9	242
Dimethyl glutarate	1119-40-0	10-30	not set	not set
Ethyl 3-ethoxypropionate	763-69-9	10-30	not set	not set
Dimethyl adipate	627-93-0	5-10	not set	not set
Dimethyl succinate	106-65-0	5-10	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

## Section 4 - First Aid Measures

### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

**Inhalation:** If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

**Skin Contact:** Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

**Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

## Section 5 - Fire Fighting Measures

**Fire and Explosion Hazards:** The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. This product is classified as a C1 combustible product. There is little risk of an explosion from this product if commercial quantities are involved in a fire. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Suitable extinguishing media are carbon dioxide, dry chemical, foam, water fog.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. Cool closed, undamaged containers exposed to fire with water spray.

**Flash point:** 64.5°C

## SAFETY DATA SHEET

Upper Flammability Limit: No data.  
 Lower Flammability Limit: No data.  
 Autoignition temperature: No data.  
 Flammability Class: C1

### Section 6 - Accidental Release Measures

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include no specific manufacturer recommendations. Use impermeable gloves with care. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours. Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Can be slippery on floors, especially when wet. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

### Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Note that this product is combustible and therefore, for Storage, meets the definition of Dangerous Goods in some states. If you store large quantities (tonnes) of such products, we suggest that you consult your state's Dangerous Goods authority in order to clarify your obligations regarding their storage.

Store packages of this product in a cool place. Make sure that containers of this product are kept tightly closed. Keep containers dry and away from water. Keep containers of this product in a well ventilated area. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further storage instructions on the label.

### Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
2-Butoxyethanol	96.9	242

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

**Skin Protection:** Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

**Protective Material Types:** There is no data that enables us to recommend any type except that it should be impermeable.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being handled commercially.

### SAFETY DATA SHEET

## Section 9 - Physical and Chemical Properties:

<b>Physical Description &amp; colour:</b>	Clear, colourless liquid.
<b>Odour:</b>	Characteristic odour.
<b>Boiling Point:</b>	Approx 100°C at 100kPa
<b>Freezing/Melting Point:</b>	No specific data. Liquid at normal temperatures.
<b>Volatiles:</b>	VOC 979g/L
<b>Vapour Pressure:</b>	No data.
<b>Vapour Density:</b>	>1
<b>Specific Gravity:</b>	0.987
<b>Water Solubility:</b>	Some, but not all ingredients are soluble.
<b>pH:</b>	No data.
<b>Volatility:</b>	> 95% (979 g/L)
<b>Odour Threshold:</b>	No data.
<b>Evaporation Rate:</b>	No data.
<b>Coeff Oil/water Distribution:</b>	No data.
<b>Autoignition temp:</b>	No data.

## Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated.

**Incompatibilities:** oxidising agents.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## Section 11 - Toxicological Information

**Toxicity:** 2-butoxyethanol is a severe eye irritant. Results of skin irritation studies are conflicting; however, it is considered to be a mild to moderate skin irritant in test animals. Contact dermatitis has been reported in a few cases. It is well absorbed via the inhalational, oral and dermal routes. Absorption studies in various species, including humans, have shown that 2-butoxyethanol is rapidly absorbed through the skin, including absorption from aqueous solutions. The respiratory uptake in volunteers in inhalational studies was approximately 57-78% of the inspired amount. Human studies indicate that dermal absorption of vapour is approximately 20% of the total vapour uptake. Following absorption, it is widely distributed throughout the body. The ingestion of large quantities of 2-butoxyethanol may result in coma, metabolic acidosis, shock and respiratory distress.

The main effect observed in both acute and repeated dose animal toxicity studies is haematotoxicity, with the principal haemolytic agent being BAA the major metabolite. Effects other than haemolysis which have been observed in repeated dose studies include changes to the liver, kidney, spleen and thymus, with these effects considered secondary to haemolysis as they are seen at levels at or above haematotoxic doses.

In fertility studies, minor changes in sperm concentration and the oestrous cycle were noted in a drinking water rat study. 2-butoxyethanol has tested negative in a wide variety of well conducted in vitro assays, including gene mutation, chromosomal aberration and DNA effect assays.

There is no data to hand indicating any particular target organs.

## Classification of Hazardous Ingredients

Ingredient	Risk Phrases
2-butoxyethanol	Conc>=25%: Xn; R20/21/22; R36/38
<b>2-Butoxyethanol:</b> LD <sub>50</sub> Oral, Rat 470mg/kg	LC <sub>50</sub> Inhalation, Rat = 2.21mg/L/4hr
<b>Dimethyl Glutarate:</b> LD <sub>50</sub> Oral, Rat 8191mg/kg	LC <sub>50</sub> Inhalation, Rat = 5.6mg/L/4hr
<b>Ethyl 3-ethoxypropionate:</b> LD <sub>50</sub> Oral, Rat 3200mg/kg	
<b>Dimethyl Adipate:</b> LD <sub>50</sub> Oral, Rat 1920mg/kg	
<b>Dimethyl Succinate:</b> LD <sub>50</sub> Oral, Rat >5000mg/kg	

## Section 12 - Ecological Information

**Ecotoxicity:** May cause long-term adverse effects in the aquatic environment.

**Persistence / Degradability:** Not available.

## SAFETY DATA SHEET

**Bioaccumulation / Accumulation:** Not available.

**Mobility in Environment:** Not available.

**Biodegradation** studies indicate that 2-butoxyethanol will be readily degraded by micro-organisms present at sewage treatment plants. Ready biodegradability tests showed that it achieved a biodegradation rate of greater than 77% after 3 days and 100% after 7 days. A 20-day biochemical oxygen demand test and an OECD 28-day closed bottle test gave it degradation rates of 75% and 88% respectively. Literature data confirm these results.

### Section 13 - Disposal Considerations

**Disposal:** This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

### Section 14 - Transport Information

**ADG Code:** This product is not classified as a Dangerous Good. No special transport conditions are necessary unless required by other regulations.

### Section 15 - Regulatory Information

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredient: 2-Butoxyethanol, is mentioned in the SUSMP.

### Section 16 - Other Information

**This MSDS contains only safety-related information. For other data see product literature.**

#### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSMP</b>	Standard for the Uniform Scheduling of Medicines & Poisons
<b>UN Number</b>	United Nations Number

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the SWA document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]  
Copyright © Nexreg Compliance Inc., May, 2012.

[www.nexreg.com](http://www.nexreg.com) Phone: (519) 488-5126

## SAFETY DATA SHEET